

## TopSerter FFcc



The TopSerter is the feeder for the separation and precise positioning of products on a target object. The products can be dispensed in cycles or continuously.

### Technical data:

Output range	up to 300 products/min
Product format	30 x 30 mm to 60 x 60 mm / other formats on request
Product thickness	5 – 25 mm
Product features	from 40 g/m <sup>2</sup> folded (paper) at least 80 g/m <sup>2</sup> (paper) other materials on request
Products	various
Positioning accuracy	+/- 1 mm (application-oriented +/- 0.1 mm)
Format settings	reproducible mechanically adjustable
Controller	freely parameterisable, recipe management
Operation / HMI	HMI 8.4" colour touch screen pushbutton on HMI HMI 280° rotatable
Indicator lights	green, orange, red (standard)
Power connection	10AT / 230V / 50/60 Hz / LNPE
Power requirement	on request
Drive	servo drive low noise various designs
Material	anodised aluminium / stainless steel
Weight	project-specific
Weight	project-specific
Mounting options	project specific design

### Options:

Product feeds	various magazine systems
Discontinued versions	project-specific outlets
Product testing	integration of camera or code reading systems
Rejection station	product rejection, project-specific
Base frame	mobile and adjustable stand, various mounting options
Safety guards	project specific design
Communication interface	I/O (standard) OPC-UA OPC-UA via Ethernet TCP/IP Industry 4.0
Validation	project specific design

If you have any questions, please do not hesitate to contact us.

Sales : +41 (0)81 257 01 00 / sales@rontech.ch